# The Bush-Whacker 8410

*2009*

## *7 Foot Rotary Cutter*




***3-point hitch***

Bush-Whacker mowers from Hall Manufacturing are increasingly in demand for agricultural, commercial and other applications where a heavy-duty, rugged mower is needed. The Bush-Whacker is available in a range of sizes to fit your needs — from the five-foot model all the way to the big 20-footer.

Hall Manufacturing has been in business for more than 75 years. During this time they've sold more than 10,000 units used across the U.S.

***optional pull type***

- **3/16" Deck**
- **Structural frame of mower is 2" by 3" tubing with 1/4" wall thickness**
- **1/4" I-Beam sides instead of 1/4" flat steel**
- **Gearbox is mounted to a 1/2" plate that is welded to the 3/16" deck**
- **6 bolt mounting on gearbox — heads are tack-welded to bottom of deck so one man can tighten the nuts or change the gearbox**

Bush-Whacker®
KICKS GRASS!

**Hall Manufacturing**
3706 East Washington • P.O. Box 5652 • North Little Rock, AR 72119
PH: 501-945-7550 • www.bush-whacker.com

Bush-Whacker®

# Model 8410 — 7 Foot Rotary Cutter

## SPECIFICATIONS*

**Gearbox — 190 HP, 540 or 1,000 RPM, Base Mounted, 1:1.47 Ratio**
Malleable housing; forged alloy steel; carburized and hardened gears and shafts; 20 splined 1 3/4" input shaft, 2 1/8" output shaft; tapered bearings; lifetime lubricated.

**Slip Clutch**
Heavy-duty spring-type adjustment with four friction discs.

**Shielded PTO — Category 4**
Made from finest quality propeller shaft materials and needle bearing universal joints.

**Blades**
1/2" material, alloy spring steel, airlift design, free swinging for long life and clean cutting. Swings back when encountering obstructions, mounted on shoulder bolts.

**Tail Wheel —**
**For 3 point hitch:** Extra heavy-duty, tapered bearings, 4" by 8" laminated puncture-proof tire.
**For pull type:** Extra heavy-duty, tapered bearings, two 6" by 9" laminated puncture-proof tires.

**Cutting Height — 2" to 13"**

**Bush-Whacker Special Deck — 3/16" Material**
Heavy-duty, one-piece electric welded frame, rolled I-Beam sides, mechanical tubing structurals.

**Rolled I-Beam Sides — 1/4" Material**
Shaped to form sides of cutter

**Chain Guards Front and Rear**

**Heavy Duty Category One or Two Hitch**

**Weight — 1380 lb.**

*These specifications are standard; however, any State Department of Transportation Specifications that may differ from standard Bush-Whacker Specifications will take precedence and be implemented into production.

WARRANTY: Guaranteed for 12 months against defective materials and workmanship. Defective parts must be returned prepaid to the factory. Guarantee is void if failure is due to operators negligence, abuse or using other than genuine Bush-Whacker parts.